AD-A243 301 NTATION PAGE

Form Approved OPM No. 0704-0188

1 hour per response, including the time for reviewing instructions, searching existing data sources gathering and maintaining the data this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington 5 Jefferson Davis Highway, Suite 1204, Ariington, VA 22202-4302, and to the C of information and Regulatory Affairs, Office of

PORT DATE

3. REPORT TYPE AND DATES COVERED

Final: 09 Nov 1990 to 01 June 1993 4. TITLE AND SUBTITLE 5. FUNDING NUMBERS Alsys, AlsyCOMP_012, Version 5.3, HP 9000s350 under HP-UX 6.5 (Host) to Motorola MVME101 (68000) with ARTK Version 5.3 (bare machine), 901116A1.11066 6. AUTHOR(S) AFNOR, Paris, FRANCE 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) 8. PERFORMING ORGANIZATION REPORT NUMBER **AFNOR** AVF-VSR-AFNOR-90-11 Tour Europe, Cedex 7 7-92080 Paris La Defense France 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) 10. SPONSORING/MONITORING AGENCY REPORT NUMBER Ada Joint Program Office United States Department of Defense Washington, D.C. 20301-3081 11. SUPPLEMENTARY NOTES Alsys, AlsyCOMP_012, Version 5.3, HP 9000s350 under HP-UX 6.5 (Host) to Motorola MVME101 (68000) with ARTK Version 5.3 (bare machine) (Target),901116A1.11066 12a DISTRIBUTION/AVAILABILITY STATEMENT 12b. DISTRIBUTION CODE Approved for public release; distribution unlimited.

13. ABSTRACT (Maximum 200 words)

Alsys, AlsyCOMP_012, Version 5.3, HP 9000s350 under HP-UX 6.5 (Host) to Motorola MVME101 (68000) with ARTK Version 5.3 (bare machine) ACVC 1.11.

> 91-17730

14. SUBJECT TERMS Ada programming language, A Capability, Val. Testing, Ada V	15. NUMBER OF PAGES 16. PRICE CODE		
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFED	UNCLASSIFIED	

. 1,

Certificate Information

The following Ada implementation was tested and determined to pass ACVC 1.11. Testing was completed on 1990-11-16.

Compiler Name and Version: AlsyCOMP_012 Version 5.3

Host Computer System:

HP 9000s350 under HP-UX 6.5

Target Computer System:

Motorola MVME101 (68000)

with ARTK Version 5.3 (bare machine)

See Section 3.1 for any additional information about the testing environment.

As a result of this validation effort, Validation Certificate 901116A1.11066 is awarded to Alsys. This certificate expires on 1992-06-01.

This report has been reviewed and is approved.

AFNOR

Philippe Alphonse

Tour Europe Cedex 7

F-92049 Paris la Défense

Ada Validation Organization

Director, Computer & Software Engineering Division

Institute for Defense Analyses

Alexandria VA 22311

Ada Woint Program Office Dr. John Solomond, Director

Department of Defense Washington DC 20301

Cost 1 de la cost de l

A Junatual Vir.

O'TEN Tab

JANUARY Dived

JANUARY Dived

JANUARY Dived

JANUARY DIVED

JUNETAL DIVERS

JUNETAL DIVERS

Ave l sad/or District

1-A

AVF Control Number: AVF-VSR-AFNOR-90-11

Ada COMPILER
VALIDATION SUMMARY REPORT:
Certificate Number: 901116A1.11066
Alsys

AlsyCOMP_012 Version 5.3
HP 9000s350 Host and Motorola MVME101 (68000) Target

Prepared By:
AFNOR
Tour Europe
Cedex 7
F-92049 Paris la Défense

DECLARATION OF CONFORMANCE

Customer: Alsys

Certificate Awardee: Alsys

Ada Validation Facility: AFNOR

ACVC Version: 1.11

Ada Implementation

Ada Compiler Name and Version: AlsyCOMP_012 Version 5.3

Host Computer System: HP 9000s350 under HP-UX 6.5

Target Computer System: Motorola MVME101 (68000)

with ARTK Version 5.3 (bare machine)

Declaration:

I the undersigned, declare that I have no knowledge of deliberate deviations from the Ada Language Standard ANSI/MIL-STD-1815A ISO 8652-1987 in the implementation listed above.

Etienne Morel

Managing Director

Alsys

- 9 NOV. 1990

Date

CONTENTS

CHAPTER	1	INTRODUCTION
	1.2	USE OF THIS VALIDATION SUMMARY REPORT 1-1 REFERENCES
CHAPTER	2	IMPLEMENTATION DEPENDENCIES
	2.2	WITHDRAWN TESTS
CHAPTER	3	PROCESSING INFORMATION
	3.2	TESTING ENVIRONMENT
APPENDI	X A	MACRO PARAMETERS
APPENDI	х в	COMPILATION SYSTEM OPTIONS
ADDENDI	v ^	ADDENDIVE OF MUE Ada CHANDADD

CHAPTER 1

INTRODUCTION

The Ada implementation described above was tested according to the Ada Validation Procedures [Pro90] against the Ada Standard [Ada83] using the current Ada Compiler Validation Capability (ACVC). This Validation Summary Report (VSR) gives an account of the testing of this Ada implementation. For any technical terms used in this report, the reader is referred to [Pro90]. A detailed description of the ACVC may be found in the current ACVC User's Guide [UG89].

1.1 USE OF THIS VALIDATION SUMMARY REPORT

Consistent with the national laws of the originating country, the Ada Certification Body may make full and free public disclosure of this report. In the United States, this is provided in accordance with the "Freedom of Information Act" (5 U.S.C. #552). The results of this validation apply only to the computers, operating systems, and compiler versions identified in this report.

The organizations represented on the signature page of this report do not represent or warrant that all statements set forth in this report are accurate and complete, or that the subject implementation has no nonconformities to the Ada Standard other than those presented. Copies of this report are available to the public from the AVF which performed this validation or from:

National Technical Information Service 5285 Port Royal Road Springfield VA 22161

Questions regarding this report or the validation test results should be directed to the AVF which performed this validation or to:

Ada Validation Organization Institute for Defense Analyses 1801 North Beauregard Street Alexandria VA 22311

INTRODUCTION

1.2 REFERENCES

- [Ada83] Reference Manual for the Ada Programming Language, ANSI/MIL-STD-1815A, February 1983 and ISO 8652-1987.
- [Pro90] Ada Compiler Validation Procedures, Version 2.1, Ada Joint Program Office, August 1990.
- [UG89] Ada Compiler Validation Capability User's Guide, 21 June 1989.

1.3 ACVC TEST CLASSES

Compliance of Ada implementations is tested by means of the ACVC. The ACVC contains a collection of test programs structured into six test classes: A, B, C, D, E, and L. The first letter of a test name identifies the class to which it belongs. Class A, C, D, and E tests are executable. Class B and class L tests are expected to produce errors at compile time and link time, respectively.

The executable tests are written in a self-checking manner and produce a PASSED, FAILED, or NOT APPLICABLE message indicating the result when they are executed. Three Ada library units, the packages REPORT and SPPRT13, and the procedure CHECK_FILE are used for this purpose. The package REPORT also provides a set of identity functions used to defeat some compiler optimizations allowed by the Ada Standard that would circumvent a test objective. The package SPPRT13 is used by many tests for Chapter 13 of the Ada Standard. The procedure CHECK_FILE is used to check the contents of text files written by some of the Class C tests for Chapter 14 of the Ada Standard. The operation of REPORT and CHECK_FILE is checked by a set of executable tests. If these units are not operating correctly, validation testing is discontinued.

Class B tests check that a compiler detects illegal language usage. Class B tests are not executable. Each test in this class is compiled and the resulting compilation listing is examined to verify that all violations of the Ada Standard are detected. Some of the class B tests contain legal Ada code which must not be flagged illegal by the compiler. This behavior is also verified.

Class L tests check that an Ada implementation correctly detects violation of the Ada Standard involving multiple, separately compiled units. Errors are expected at link time, and execution is attempted.

In some tests of the ACVC, certain macro strings have to be replaced by implementation-specific values -- for example, the largest integer. A list of the values used for this implementation is provided in Appendix A. In addition to these anticipated test modifications, additional changes may be required to remove unforeseen conflicts between the tests and implementation-dependent characteristics. The modifications required for this implementation are described in section 2.3.

For each Ada implementation, a customized test suite is produced by the AVF. This customization consists of making the modifications described in the preceding paragraph, removing withdrawn tests (see section 2.1) and, possibly some inapplicable tests (see Section 2.2 and [UG89]).

In order to pass an ACVC an Ada implementation must process each test of the customized test suite according to the Ada Standard.

1.4 DEFINITION OF TERMS

Ada Compiler

The software and any needed hardware that have to be added to a given host and target computer system to allow transformation of Ada programs into executable form and execution thereof.

Ada Compiler Validation Capability (ACVC)

The means for testing compliance of Ada implementations, consisting of the test suite, the support programs, the ACVC user's guide and the template for the validation summary report.

An Ada compiler with its host computer system and its Ada Implementation target computer system.

Ada Validation

The part of the certification body which carries out the procedures required to establish the compliance of an Ada Facility (AVF) implementation.

Ada Validation Organization (AVO)

The part of the certification body that provides technical guidance for operations of the Ada certification system.

Compliance of The ability of the implementation to pass an ACVC version. an Ada Implementation

Computer System

A functional unit, consisting of one or more computers and associated software, that uses common storage for all or part of a program and also for all or part of the data necessary for the execution of the program; user-written or user-designated programs; performs user-designated data manipulation, including arithmetic operations and logic operations; and that can execute programs that modify themselves during execution. computer system may be a stand-alone unit or may consist of several inter-connected units.

Conformity Fulfillment by a product, process or service of all requirements specified.

INTRODUCTION

Customer

An individual or corporate entity who enters into an agreement with an AVF which specifies the terms and conditions for AVF services (of any kind) to be performed.

Declaration of A formal statement from a customer assuring that conformity Conformance is realized or attainable on the Ada implementation for which validation status is realized.

System

Host Computer A computer system where Ada source programs are transformed into executable form.

Inapplicable test

A test that contains one or more test objectives found to be irrelevant for the given Ada implementation.

Operating System

Software that controls the execution of programs and that provides services such as resource allocation, scheduling, input/output control, and data management. Usually, operating systems are predominantly software, but partial or complete hardware implementations are possible.

Target Computer System

A computer system where the executable form of Ada programs are executed.

Compiler

Validated Ada The compiler of a validated Ada implementation.

Validated Ada An Ada implementation that has been validated successfully Implementation either by AVF testing or by registration [Pro90].

Validation

The process of checking the conformity of an Ada compiler to the Ada programming language and of issuing a certificate for this implementation.

Withdrawn test

A test found to be incorrect and not used in conformity testing. A test may be incorrect because it has an invalid test objective, fails to meet its test objective, or contains erroneous or illegal use of the Ada programming language.

CHAPTER 2

IMPLEMENTATION DEPENDENCIES

2.1 WITHDRAWN TESTS

The following tests have been withdrawn by the AVO. The rationale for withdrawing each test is available from either the AVO or the AVF. The publication date for this list of withdrawn tests is 90-10-12.

E28005C	B28006C	C34006D	B41308B	C43004A	C45114A
C45346A	C45612B	C45651A	C46022A	B49008A	A74006A
B83022B	B83022H	B83025B	B83025D	B83026B	B85001L
C83026A	C83041A	C97116A	C98003B	BA2011A	CB7001A
CB7001B	CB7004A	CC1223A	BC1226A	CC1226B	BC3009B
AD1B08A	BD2A02A	CD2A21E	CD2A23E	CD2A32A	CD2A41A
CD2A41E	CD2A87A	CD2B15C	BD3006A	CD4022A	CD4022D
CD4024B	CD4024C	CD4024D	CD4031A	CD4051D	CD5111A
CD7004C	ED7005D	CD7005E	AD7006A	CD7006E	AD7201A
AD7201E	CD7204B	BD8002A	BD8004C	CD9005A	CD9005B
CDA201E	CE21071	CE2119B	CE2205B	CE2405A	CE3111C
CE3118A	CE3411B	CE3412B	CE3812A	CE3814A	CE3902B
BD1B02B	BD1B06A	C74308A	BD4008A	CE2117A	CE2117B
CE3607B	CE3607C	CE3607D			

2.2 INAPPLICABLE TESTS

A test is inapplicable if it contains test objectives which are irrelevant for a given Ada implementation. Reasons for a test's inapplicability may be supported by documents issued by ISO and the AJPO known as Approved Ada Commentaries and commonly referenced in the format AI-ddddd. For this implementation, the following tests were determined to be inapplicable for the reasons indicated; references to Ada Commentaries are included as appropriate.

The following 201 tests have floating-point type declarations requiring more digits than SYSTEM.MAX_DIGITS :

C24113L..Y C35705L..Y C35706L..Y C35707L..Y C35708L..Y C35802L..Z C45241L..Y C45321L..Y C45421L..Y C45521L..Z C45524L..Z C45621L..Z C45641L..Y C46012L..Z

The following 21 tests check for predefined type LONG INTEGER:

C35404C	C45231C	C45304C	C45411C	C45412C
C45502C	C45503C	C45504C	C45504F	C45611C
C45612C	C45613C	C45614C	C45631C	C45632C
B52004D	C55B07A	B55B09C	B86001W	C86006C
CD7101F				

IMPLEMENTATION DEPENDENCIES

C35702A C35713B C45423B B86001T C86006H check for predefined type SHORT_FLOAT.

C35713D B86001Z check for a predefined floating-point type with a name other than FLOAT, SHORT_FLOAT or LONG_FLOAT.

C45531M..P C45532M..P check fixed-point operations for types that require a SYSTEM.MAX_MANTISSA of 47 or greater.

C45536A C46013B C46031B C46033B C46034B contain 'SMALL representation clauses which are not powers of two or ten.

C45624A and C45624B check that the proper exception is raised if MACHINE_OVERFLOWS is FALSE for floating point types; for this implementation, MACHINE_OVERFLOWS is TRUE.

C86001F recompiles package SYSTEM, making package TEXT_IO, and hence package REPORT, obsolete. For this implementation, the package TEXT_IO is dependent upon package SYSTEM.

B86001Y checks for a predefined fixed-point type other than DURATION.

CD1009C uses a representation clause specifying a non-default size for a floating-point type.

CD2A53A checks operations of a fixed-point type for which a length clause specifies a power-of-ten type'small. [See 2.3.]

CD2A84A, CD2A84E, CD2A84I..J (2 tests), and CD2A84O use representation clauses specifying non-default sizes for access types.

BD8001A, BD8003A, BD8004A..B (2 tests), and AD8011A use machine code insertions.

CE2103A, CE2103B, and CE3107A expect that NAME_ERROR is raised when an attempt is made to create a file with an illegal name; this implementation does not support the creation of external files and so raises USE_ERROR. (See 2.3.)

IMPLEMENTATION DEPENDENCIES

The following 265 tests check for sequential, text, and direct access files:

CE2102AC	,	CE2102GH	(2)	CE2102K		CE2102NY	(12)
CE2103CD	(2)	CE2104AD	(4)	CE2105AB	(2)	CE2106AB	(2)
CE2107AH	(8)	CE2107L		CE2108AH	(8)	CE2109AC	(3)
CE2110AD	(4)	CE2111AI	(9)	CE2115AB	(2)		
CE2120AB	(2)	CE2201AC	(3)	EE2201DE	(2)	CE2201FN	(9)
CE2203A		CE2204AD	(4)	CE2205A		CE2206A	
CE2208B		CE2401AC	(3)	EE2401D		CE2401EF	(2)
EE2401G		CF2401HL	(5)	CE2403A		CE2404AP	(2)
CE2405B		CE2406A		CE2407AB	(2)	CE2408AB	(2)
CE2409AB	(2)	CE2410AB	(2)	CE2411A		CE3102AC	(3)
CE3102FH	(3)	CE3102JK	(2)	CE3103A		CE3104AC	
CE3106AB	(2)	CE3107B		CE3108AB	(2)	CE3109A	
CE3110A		CE3111AB	(2)	CE3111DE	(2)	CE3112AD	(4)
CE3114AB	(2)	CE3115A		CE3116A		CE3119A	•
EE3203A		EE3204A		CE3207A		CE3208A	
CE3301A		EE3301B		CE3302A		CE3304A	
CE3305A		CE3401A		CE3402A		EE3402B	
CE3402CD	(2)	CE3403AC	(3)	CE3403EF	(2)	CE3404BD	(3)
CE3405A		EE3405B		CE3405CD	(2)	CE3406AD	(4)
CE3407AC	(3)	CE3408AC	(3)	CE3409A		CE3409CE	(3)
EE3409F		CE3410A		CE3410CE	(3)	EE3410F	
CE3411A		CE3411C		CE3412A		EE3412C	
CE3413AC	(3)	CE3414A		CE3602AD	(4)	CE3603A	
CE3604AB	(2)	CE3605AE	(5)	CE3606AB	(2)		
CE3704AF	(6)	CE3704MO	(3)	CE3705AE	(5)	CE3706D	
CE3706FG	(2)			CE3805AB	(2)	CE3806AB	(2)
CE3806DE	(2)	CE3806GH	(2)	CE3904AB	(2)	CE3905AC	(3)
CE3905L		CE3906AC	(3)	CE3906EF	(2)		•

2.3 TEST MODIFICATIONS

Modifications (see section 1.3) were required for 28 tests.

The following 22 tests were split into two or more tests because this implementation did not report the violations of the Ada Standard in the way expected by the original tests:

B23004A B24007A B24009A B28003A B32202A B32202B B32202C B36307A B37004A B61012A B62001B B74304B B74304C B74401F B74401R B91004A B95032A B95069A B95069B BA1101B BC2001D BC3009C

IMPLEMENTATION DEPENDENCIES

BA2001E was graded passed by Evaluation Modification as directed by the AVO. The test expects that duplicate names of subunits with a common ancestor will be detected as compilation errors; this implementation detects the errors at link time, and the AVO ruled that this behavior is acceptable.

EA3004D was graded passed by Evaluation and Processing Modification as directed by the AVO. The test requires that either pragma INLINE is obeyed for the invocation of a function in each of three contexts and that thus three library units are made obsolete by the re-compilation of the inlined function's body, or else the pragma is ignored completely. This implementation obeys the pragma except when the invocation is within a package specification. When the test's files are processed in the given order, only two units are made obsolete; thus, the expected error at line 27 of file EA3004D6M is not valid and is not flagged. To confirm that indeed the pragma is not obeyed in this one case, the test was also processed with the files re-ordered so that the re-compilation follows only the package declaration (and thus the other library units will not be made obsolete, as they are compiled later); a "NOT APPLICABLE" result was produced, as expected. The revised order of files was 0-1-4-5-2-3-6.

CD2A53A was graded inapplicable by Evaluation Modification as directed by the AVO. The test contains a specification of power-of-10 value as small for a fixed-point type. The AVO ruled that, under ACVC 1.11, support of decimal smalls may be omitted.

CE2103A, CE2103B, and CE3107A were graded inapplicable by Evaluation Modification as directed by the AVO. The tests abort with an unhandled exception when USE_ERROR is raised on the attempt to create an external file, which is acceptable behavior because this implementation does not support the creation of external files (cf AI-00332).

CHAPTER 3

PROCESSING INFORMATION

3.1 TESTING ENVIRONMENT

The configuration in which the testing was performed is described by the following designations of hardware and software components:

Host computer: HP 9000s350 Host operating system: HP-UX 6.5

Target computer:

Board: Motorola MVME101 CPU: Motorola MC68000

Coprocessor: none

I/O: Motorola MC68661 Timer: Motorola MC6840

Bus: VMEbus Memory size: 1 Mb

Downloader: AdaTransfer, Version 5.3

Communication link: RS 232 serial connection

For a point of contact for technical information about this Ada implementation system, see:

Didier De Bie Alsys SA 29, Avenue Lucien-Rene Duchesne 78170 La Celle Saint-Cloud France

For a point of contact for sales information about this Ada implementation system, see:

Bob Lamkin Philippe Loutrel Alsys Inc Alsys SA

67 South Bedford Street

Burlington

29, Avenue Lucien-Rene Duchesne
78170 La Celle Saint-Cloud

MA 01803-5152 France

U.S.A.

John Stewart Kurt Wey
Alsys Ltd Alsys Gmbh
Partridge House Am Ruppurer Schoss 7
Newtown Road D-7500 Karlsruhe 51

Henley-on-Thames Germany

Oxon, RG9 1EN

U.K.

PROCESSING INFORMATION

Jun Shimura
Alsys-KKE Co. Ltd
Techno-Wave 16F
1-1-25 Shin-Urashima-cho
Kanagawa-Ku
Yokohama
Japan

Orjan Leringe
Alys AB
Patron Pehr Vag 10
Box 1085
141 22 Huddinge
Stockholm
Sweden

Testing of this Ada implementation was conducted at the customer's site by a validation team from the AVF.

3.2 SUMMARY OF TEST RESULTS

An Ada Implementation passes a given ACVC version if it processes each test of the customized test suite in accordance with the Ada Programming Language Standard, whether the test is applicable or inapplicable; otherwise, the Ada Implementation fails the ACVC [Pro89].

For all processed tests (inapplicable and applicable), a result was obtained that conforms to the Ada Programming Language Standard.

a)	Total Number of Applicable Tests	3563	
•	Total Number of Withdrawn Tests	81	
c)	Processed Inapplicable Tests	60	
d)	Non-Processed I/O Tests	265	
e)	Non-Processed Floating-Point		
	Precision Tests	201	
f)	Total Number of Inapplicable Tests	526	(c+d+e)

- g) Total Number of Tests for ACVC 1.11 4170 (a+b+f)

The above number of I/O tests were not processed because this implementation does not support a file system. The above number of floating-point tests were not processed because they used floating-point precision exceeding that supported by the implementation. When this compiler was tested, the tests listed in section 2.1 had been withdrawn because of test errors.

3.3 TEST EXECUTION

Version 1.11 of the ACVC comprises 4170 tests. When this compiler was tested, the tests listed in section 2.1 had been withdrawn because of test errors. The AVF determined that 526 tests were inapplicable to this implementation. All inapplicable tests were processed during validation testing except for 201 executable tests that use floating-point precision exceeding that supported by the implementation and 265 executable tests that use file operations not supported by the implementation. In addition, the modified tests mentioned in section 2.3 were also processed.

A Data Cartridge Tape containing the customized test suite (see section 1.3) was taken on-site by the validation team for processing. The contents of the Data Cartridge Tape were loaded directly onto the host computer.

After the test files were loaded onto the host computer, the full set of tests was processed by the Ada implementation.

The tests were compiled and linked on the host computer system, as appropriate. The executable images were transferred to the target computer system by the communications link described above, and run. The results were captured on the host computer system.

Testing was performed using command scripts provided by the customer and reviewed by the validation team. See Appendix B for a complete listing of the processing options for this implementation. It also indicates the default options.

Test output, compiler and linker listings, and job logs were captured on Data Cartridge Tape and archived at the AVF. The listings examined on-site by the validation team were also archived.

APPENDIX A

MACRO PARAMETERS

This appendix contains the macro parameters used for customizing the ACVC. The meaning and purpose of these parameters are explained in [UG89]. The parameter values are presented in two tables. The first table lists the values that are defined in terms of the maximum input-line length, which is the value for \$MAX_IN_LEN--also listed here. These values are expressed here as Ada string aggregates, where "V" represents the maximum input-line length.

Macro Parameter	Macro Value
\$BIG_ID1	(1V-1 => 'A', V => '1')
\$BIG_ID2	(1V-1 => 'A', V => '2')
\$BIG_ID3	$(1V/2 \Rightarrow 'A') & '3' & (1V-1-V/2 \Rightarrow 'A')$
\$BIG_ID4	$(1V/2 \Rightarrow 'A') & '4' & (1V-1-V/2 \Rightarrow 'A')$
\$BIG_INT_LIT	(1V-3 => '0') & "298"
\$BIG_REAL_LIT	(1V-5 => '0') & "690.0"
\$BIG_STRING1	'"' & (1V/2 => 'A') & '"'
\$BIG_STRING2	'"' & (1V-1-V/2 => 'A') & '1' & '"'
\$BLANKS	(1V-20 => ' ')
\$MAX_LEN_INT_BASED_LI	FERAL "2:" & (1V-5 => '0') & "11:"
\$MAX_LEN_REAL_BASED_L	ITERAL "16:" & (1V-7 => '0') & "F.E:"
\$MAX_STRING_LITERAL	'"' & (1V-2 => 'A') & '"'

MACRO PARAMETERS

The following table lists all of the other macro parameters and their respective values.

Macro Parameter	Macro Value
\$MAX_IN_LEN	255
ACC_SIZE	32
\$ALIGNMENT	2
\$COUNT_LAST	2147483647
SDEFAULT_MEM_SIZE	2**32
SDEFAULT_STOR_UNIT	8
\$DEFAULT_SYS_NAME	MC680X0
\$DELTA_DOC	2#1.0#E-31
\$ENTRY_ADDRESS	INTERRUPT_ADDRESS
\$ENTRY_ADDRESS1	INTERRUPT_ADDRESS1
\$ENTRY_ADDRESS2	INTERRUPT_ADDRESS2
\$FIELD_LAST	253
\$FILE_TERMINATOR	CHARACTER' VAL (32)
\$FIXED_NAME	NO_SUCH_TYPE
\$FLOAT_NAME	NO_SUCH_TYPE
\$FORM_STRING	ल सं
\$FORM_STRING2	"CANNOT_RESTRICT_FILE_CAPACITY"
\$GREATER_THAN_DURATION	100_000.0
\$GREATER_THAN_DURATION_BASE_LAS	ST 100_000_000.0
\$GREATER_THAN_FLOAT_BASE_LAST	2.0E128
\$GREATER_THAN_FLOAT_SAFE_LARGE	2#1.11111111111111111111111111111111111

\$GREATER_THAN_SHORT_FLOAT_SAFE_LARGE 1.0E308

\$HIGH_PRIORITY 24

\$ILLEGAL EXTERNAL FILE_NAME1 /~/*/f1

\$ILLEGAL EXTERNAL FILE_NAME2 /~/*/f2

\$INAPPROPRIATE_LINE_LENGTH -1

\$INAPPROPRIATE_PAGE_LENGTH -1

\$INCLUDE PRAGMA1 PRAGMA INCLUDE ("A28006D1.TST")

\$INCLUDE PRAGMA2 PRAGMA INCLUDE ("B28006D1.TST")

\$INTEGER FIRST -2147483648

\$INTEGER_LAST 2147483647

\$INTEGER_LAST_PLUS_1 2_147_483_648

\$INTERFACE_LANGUAGE C

SLESS THAN DURATION -100 000.0

\$LESS_THAN_DURATION_BASE_FIRST -100_000_000.0

\$LINE TERMINATOR ASCII.LF

\$LOW_PRIORITY 1

\$MACHINE_CODE_STATEMENT NULL;

\$MACHINE_CODE_TYPE NO_SUCH_TYPE

\$MANTISSA_DOC 31

\$MAX_DIGITS 15

\$MAX INT 2147483647

\$MAX_INT_PLUS_1 2_147_483_648

\$MIN_INT -2147483648

\$NAME SHORT_SHORT_INTEGER

SNAME_LIST MC680X0

\$NAME_SPECIFICATION1 /platon2/v1.11work/com/X2120A

\$NAME_SPECIFICATION2 /platon2/v1.11work/com/X2120B

\$NAME_SPECIFICATION3 /platon2/v1.11work/com/X3119A

\$NEG_BASED_INT 16#FFFFFFE#

\$NEW MEM_SIZE 2**32

\$NEW_STOR_UNIT 8

\$NEW_SYS_NAME MC680X0

\$PAGE_TERMINATOR ASCII.FF

\$RECORD_NAME NO_SUCH_MACHINE_CODE_TYPE

STASK_SIZE 32

\$TASK_STORAGE_SIZE 4096

\$TICK 0.02

\$VARIABLE_ADDRESS OBJECT_ADDRESS

\$VARIABLE_ADDRESS1
OBJECT_ADDRESS1

\$VARIABLE_ADDRESS2 OBJECT_ADDRESS2

\$YOUR_PRAGMA INTERFACE_NAME

APPENDIX B

OPTIONS

The options of this Ada implementation, as described in this Appendix, are provided by the customer. Unless specifically noted otherwise, references in this appendix are to compiler documentation and not to this report.

COMPILATION SYSTEM OPTIONS

ERRORS=999: allow 999 errors before terminating compilation (default 50).

CALLS=INLINED: allow inline insertion of code for subprograms and take pragma INLINE into account. (default NORMAL).

REDUCTION=PARTIAL: perform some high level optimizations on checks and loops. (default NONE).

EXPRESSIONS=PARTIAL: perform some low level optimisations on common subexpressions and register allocations (default NONE).

FLOAT=SOFTWARE: Floating point operations are done by software (default).

NOWARNING: Do not generate warning messages

NODETAIL: Do not include extra detail in error messages

SHOW=NONE: No banner header on listing pages, no error

summary at end of listing.

FILEWIDTH=120: Listing file has 120 characters per line

NOFILELENGTH: Unpaginated listing file

For tests rejected at compile time:

TEXT: compilation listing including full source text (with embedded error messages)

For tests compiled without errors:

NOTEXT: compilation listing including only source text for

lines containg errors

(i.e. empty listing if no errors)

LINKER OPTIONS

FLOAT=SOFTWARE: Floating point operations are done by software (default).

ROM=NO: program can't be put in ROM (default).

DIRECTIVES=pgm101.cmd

SEARCH=user101.a

KERNEL-USER: Working mode of the processor (default)

SEGMENTED=NO: Do not generate a section per compilation

unit (default).

NOWARNING: Do not generate warning messages

FILEWIDTH=80: Listing file has 80 characters per line

NOFILELENGTH: Unpaginated listing file

APPENDIX C

APPENDIX F OF THE Ada STANDARD

The only allowed implementation dependencies correspond to implementation-dependent pragmas, to certain machine-dependent conventions as mentioned in Chapter 13 of the Ada Standard, and to certain allowed restrictions on representation clauses. The implementation-dependent characteristics of this Ada implementation, as described in this Appendix, are provided by the customer. Unless specifically noted otherwise, references in this Appendix are to compiler documentation and not to this report. Implementation-specific portions of the package STANDARD, which are not a part of Appendix F, are:

```
package STANDARD is
```

Alsys Ada Compiler

APPENDIX F

for Compilers Targeted to Motorola 68K

Version 5.3

Alsys S.A. 29, Avenue Lucien-René Duchesne 78170 La Celle St. Cloud, France

Alsys Inc. 67 South Bedford Street Burlington, MA 01803-5152, U.S.A.

Alsys Ltd
Partridge House, Newtown Road
Henley-on-Thames,
Oxfordshire RG9 1EN, U.K.

Alsys AB Patron Pehr Väg 10 Box 1085 141 22 Huddinge, Stockholm, Sweden

Copyright 1990 by Alsys

All rights reserved. No part of this document may be reproduced in any form or by any means without permission in writing from Alsys.

Printed: November 9, 1990

Alsys reserves the right to make changes in specifications and other information contained in this publication without prior notice. Consult Alsys to determine whether such changes have been made.

HP-UX is a trademark of Hewlett Packard

Sun Workstation is a registered trademark of Sun Microsystems, Inc.

UNIX is a registered trademark of AT&T BELL LABORATORIES.

Apollo and DOMAIN are registered trademarks of Apollo Computer Inc.

AEGIS and DOMAIN/IX are registered trademarks of Apollo Computer Inc.

Macintosh, Mac, and A/UX are trademarks of Apple Computer, Inc.

Cetia, Unigraph and Unigraph/X are registered trademarks of Cetia.

Alsys, AdaWorld, AdaProbe, AdaTune, AdaXref, AdaReformat, and AdaMake are registered trademarks of Alsys.

TABLE OF CONTENTS

PRE	FACE	v
1	IMPLEMENTATION-DEPENDENT PRAGMAS	7
1.1	The Pragma INTERFACE	7
1.2	The Pragma INTERFACE_NAME	7
1.3	The Pragma INLINE	8
1.4	The Pragma EXPORT	8
1.5	The Pragma EXTERNAL_NAME	9
1.6	The Pragma INDENT	9
1.7	The Pragma IMPROVE	10
1.8	The other Pragmas	10
1.9	Pragmas with no Effect	10
2	IMPLEMENTATION-DEPENDENT ATTRIBUTES	11
2.1	Attributes used in Record Representation Clauses	12
2.2	Limitations on the use of the Attribute ADDRESS	12
2.3	The Attribute IMPORT	12
3	THE PACKAGE SYSTEM	13
4	TYPE REPRESENTATION CLAUSES	18
4.1	Enumeration Types	18
4.2	Integer Types	19
4.3	Floating Point Types	20
4.4	Fixed Point Types	21
4.5	Access Types	22
4.6	Task Types	23
4.7	Array Types	23
4.8	Record Types	24

5	IMPLEMENTATION-DEPENDENT COMPONENTS	28
6	ADDRESS CLAUSES	29
5.1	Address Clauses for Objects	29
5.2	Address Clauses for Program Units	29
5.3	Address Clauses for Entries	29
7	UNCHECKED CONVERSIONS	30
8	INPUT-OUTPUT CHARACTERISTICS	31
3.1	Introduction	31
3.2	The Parameter FORM	32

PREFACE

This is the "Appendix F, Implementation-Dependent Characteristics" of the Reference Manual for the Ada Programming Language, ISO/8652-1987.

CHAPTER 1

IMPLEMENTATION-DEPENDENT PRAGMAS

1.1 The Pragma INTERFACE

Programs written in Ada can interface with external subprograms written in another language, by use of the pragma INTERFACE. The format of the pragma is:

pragma INTERFACE (language_name, Ada_subprogram_name);

The language_name may be Assembler, C, Fortran or Pascal depending on the Alsys Ada compiler used (see Application Developer's Guide).

The Ada_subprogram_name is the name by which the subprogram is known in Ada.

Interfacing the Ada language with other languages is detailed in the Application Developer's Guide.

1.2 The Pragma INTERFACE_NAME

To name the external subprogram to which an Ada subprogram is interfaced, as defined in the other language, may require the use of non-Ada naming conventions, such as special characters, or case sensitivity. For this purpose the implementation-dependent pragma INTERFACE NAME may be used in conjunction with the pragma INTERFACE.

pragma INTERFACE_NAME (Ada_subprogram_name, name_string);

The name_string is a string, which denotes the name of the external subprogram as defined in the other language. The Ada_subprogram_name is the name by which the subprogram is known in Ada.

The pragma INTERFACE_NAME may be used anywhere in an Ada program where INTERFACE is allowed (see [13.9]). It must occur after the corresponding pragma INTERFACE and within the same declarative part or package specification.

1.3 The Pragma INLINE

Pragma INLINE is fully supported; however, it is not possible to inline a subprogram in a declarative part.

Note that inlining facilities are also provided by use of the command COMPILE with the option IMPROVE (see the *User's Guide*).

1.4 The Pragma EXPORT

The pragma EXPORT takes a language name and an Ada identifier as arguments. This pragma allows an object defined in Ada to be visible to external programs written in the specified language.

```
pragma EXPORT (language_name, Ada_identifier)
```

Example:

```
package MY_PACKAGE is
```

```
THIS_OBJECT: INTEGER; pragma EXPORT (PASCAL, THIS_OBJECT);
```

end MY PACKAGE;

Limitations on the use of pragma EXPORT

- This pragma must occur in a declarative part and applies only to objects declared in this same declarative part, that is, generic instantiated objects or renamed objects are excluded.
- The pragma is only to be used for objects with direct allocation mode, which are
 declared in a library package. The ALSYS implementation gives indirect allocation
 mode to dynamic objects, and objects that have a significant size (see Section 2.1 of
 the Application Developer's Guide).

1.5 The Pragma EXTERNAL_NAME

To name an exported Ada object as it is identified in the other language may require the use of non-Ada naming conventions, such as special characters, or case sensitivity. For this purpose the implementation-dependent pragma EXTERNAL_NAME may be used in conjunction with the pragma EXPORT:

```
pragma EXTERNAL_NAME (Ada_identifier, name_string);
```

The name_string is a string which denotes the name of the identifier defined in the other language. The Ada_identifier denotes the exported Ada object.

The pragma EXTERNAL_NAME may be used anywhere in an Ada program where pragma EXPORT is allowed. It must occur after the corresponding pragma EXPORT and within the same library package.

Example:

```
package MY_PACKAGE is

THIS_OBJECT: INTEGER;
pragma EXPORT (PASCAL, THIS_OBJECT);
pragma EXTERNAL_NAME (THIS_OBJECT, "ThisObject");
......
end MY_PACKAGE;
```

1.6 The Pragma INDENT

This pragma is only used by AdaReformat. This tool offers the functionalities of a pretty-printer in an Ada environment.

The pragma is placed in the source file and interpreted by AdaReformat.

pragma INDENT(OFF) causes AdaReformat not to modify the source lines after this pragma.

pragma INDENT(ON) causes AdaReformat to resume its action after this pragma.

1.7 The Pragma IMPROVE

This pragma is used to suppress implicit components from a record type.

pragma IMPROVE (TIME | SPACE, [ON =>] simple_name);

See Section 4.8 for the complete description.

1.8 The other Pragmas

Pragma PACK is discussed in detail in the section on representation clauses and records (Chapter 4).

Pragma PRIORITY is accepted with the range of priorities running from 1 to 16 (see the definition of the predefined package SYSTEM in Section 3). Undefined priority (no pragma PRIORITY) is treated as though it were less than every defined priority value.

In addition to pragma SUPPRESS, it is possible to suppress all checks in a given compilation by the use of the Compiler option CHECKS. (See Chapter 4 of the *User's Guide.*)

1.9 Pragmas with no Effect

The following pragmas have no effect:

CONTROLLED MEMORY_SIZE STORAGE_UNIT SYSTEM_NAME OPTIMIZE

For optimization, certain facilities are provided through use of the command COMPILE with the option IMPROVE (see the *User's Guide*).

CHAPTER 2

IMPLEMENTATION-DEPENDENT ATTRIBUTES

Throughout this chapter and the remaining chapters of this document three special types of integer are used in the text. They are used where the number of bits used to store the integer is important.

The three types used are defined as:

```
INTEGER_8; an integer stored in 8 bits,
```

INTEGER_16; an integer stored in 16 bits,

INTEGER_32; an integer stored in 32 bits.

and can be respectively declared, with representation clauses, thus:

```
type INTEGER_8 is new INTEGER range -2**7 .. 2**7 -1; for INTEGER_8'SIZE use 8;
```

```
type INTEGER_16 is new INTEGER range -2**15 .. 2**15 -1; for INTEGER_16'SIZE use 16;
```

```
type INTEGER_32 is new INTEGER range -2**31 .. 2**31 -1; for INTEGER_32'SIZE use 32;
```

The user gains complete control over the data storage by using these forms of declaration, as opposed to those defined in package STANDARD over which the user has no control. (Refer to Chapter 3 of this document.)

2.1 Attributes used in Record Representation Clauses

In addition to the Representation Attributes of [13.7.2] and [13.7.3], the following five attributes are used to form names of indirect and implicit components for use in record representation clauses, as described in Section 4.8.

'OFFSET
'RECORD_SIZE
'VARIANT_INDEX
'ARRAY_DESCRIPTOR
'RECORD_DESCRIPTOR

2.2 Limitations on the use of the Attribute ADDRESS

The attribute ADDRESS is implemented for all prefixes that have meaningful addresses.

Note: The value returned by the attribute ADDRESS is undefined before the elaboration of the subprogram body (when 'ADDRESS is applied to a subprogram).

The following entities do not have meaningful addresses and will therefore cause a compilation error if used as prefix to ADDRESS:

- A constant that is implemented as an immediate value, i.e., does not have any space allocated for it
- A package specification that is not a library unit
- A package body that is not a library unit or subunit
- A function that renames an enumeration literal.

2.3 The Attribute IMPORT

This attribute is a function which takes two literal strings as arguments; the first one denotes a language name and the second one denotes an external symbol name. It yields the address of this external symbol. The prefix of this attribute must be SYSTEM.ADDRESS. The value of this attribute is of the type SYSTEM.ADDRESS. The syntax is:

SYSTEM.ADDRESS'IMPORT ("Language_name", "external_symbol_name")

CHAPTER 3

THE PACKAGE SYSTEM

This section contains information on the visible part of the specification of the package SYSTEM

package SYSTEM is

-- Standard Ada definitions

-- Address operations

function VALUE (LEFT: in STRING) return ADDRESS; -- Converts a string into an address. -- The string can represent either an unsigned address ie. -- "16#XXXXXXXX#" where XXXXXXXX is in the range -- 0..FFFFFFFF, or a signed address ie. -- "-16#XXXXXXXX#" where XXXXXXXX is in the range -- 0..7FFFFFFF. -- A CONSTRAINT ERROR is raised if the string does not conform to -- this syntax ADDRESS WIDTH: constant := 3 + 8 + 1; subtype ADDRESS_STRING is STRING(1..ADDRESS_WIDTH); function IMAGE(LEFT: in ADDRESS) return ADDRESS_STRING; -- Converts an address to a string. The syntax of the returned string is -- described in the VALUE function above. Refer to the unsigned -- representation. type OFFSET is range -2**31 .. 2**31 -1; - This type is used to measure a number of storage units (bytes). -- The type is an Ada integer type. function SAME_SEGMENT (LEFT, RIGHT: in ADDRESS) return BOOLEAN; -----On a segmented architecture the function returns TRUE if the two -- addresses have the same segment value. On a non-segmented -- architecture it always returns TRUE.

ADDRESS_ERROR: exception;

- -- This exception is raised by "<", "<=", ">", ">=" and "-" if the two
- -- addresses do not have the same segment value. This exception is
- -- never raised on a non-segmented machine.
- -- The exception CONSTRAINT_ERROR can be raised by "+" and "-".

function "+" (LEFT: in OFFSET; RIGHT: in ADDRESS) return ADDRESS:

function "+" (LEFT: in ADDRESS; RIGHT: in OFFSET)

return ADDRESS; function "-" (LEFT: in ADDRESS; RIGHT: in OFFSET) return ADDRESS;-----

- -- These routines provide support to perform address computations. The
- -- meaning of the "+" and "-" operators is architecture dependent. For
- -- example on a segmented machine the OFFSET parameter is added to,
- -- or subtracted from the offset part of the address, the segment
- -- remaining unaltered.

function "-" (LEFT: in ADDRESS; RIGHT: in ADDRESS) return OFFSET:

- -- Returns the distance between the given addresses. The result is
- -- signed. The exception ADDRESS_ERROR is raised on a segmented
- -- architecture if the two addresses do not have the same segment value.

function "<" (LEFT, RIGHT: in ADDRESS)

return BOOLEAN;

function "<=" (LEFT, RIGHT: in ADDRESS)

return BOOLEAN;

function ">" (LEFT, RIGHT: in ADDRESS)

return BOOLEAN;

function ">=" (LEFT, RIGHT: in ADDRESS) return BOOLEAN; -- Perform a comparison on addresses, or on the offset part of addresses -- for a segmented machine. The comparison is unsigned on all -- machines except the Transputer. function "mod" (LEFT: in ADDRESS; RIGHT: in POSITIVE) return NATURAL: -- Returns the offset of LEFT relative to the memory block immediately -- below it starting at a multiple of RIGHT storage units. On a -- segmented machine, the segment part is ignored. type ROUND_DIRECTION is (DOWN, UP); function ROUND (VALUE: in ADDRESS; **DIRECTION: in ROUND DIRECTION;** MODULUS: in POSITIVE) return ADDRESS; -- Returns the given address rounded to a specific value. generic type TARGET is private; function FETCH_FROM_ADDRESS (A: in ADDRESS) return TARGET; generic type TARGET is private; procedure ASSIGN TO ADDRESS (A: in ADDRESS; T: in TARGET); -- These routines are provided to perform READ/WRITE operations in -- memory. These routines may give unexpected results if used with -- unconstrained types.

type OBJECT_LENGTH is range 0 .. 2**31 - 1;

-- This type is used to designate the size of an object in storage units.

procedure MOVE (

TO: in ADDRESS;

FROM: in ADDRESS;

LENGTH: in OBJECT_LENGTH);

- -- Copies LENGTH storage units starting at the address FROM to the
- -- address TO. The source and destination may overlap.
- -- Use of this procedure with optimizers may lead to unexpected
- -- results.

private

-- private part of the system

end SYSTEM;

TYPE REPRESENTATION CLAUSES

The aim of this section is to explain how objects are represented and allocated by the Alsys . Ja compiler for MC680X0 machines and how it is possible to control this using representation clauses.

The representation of an object is closely connected with its type. For this reason this section addresses successively the representation of enumeration, integer, floating point, fixed point, access, task, array and record types. For each class of type the representation of the corresponding objects is described.

Except in the case of array and record types, the description for each class of type is independent of the others. To understand the representation of an array type it is necessary to understand first the representation of its components. The same rule applies to record types.

Apart from implementation defined pragmas, Ada provides three means to control the size of objects:

- a (predefined) pragma PACK, when the object is an array, an array component, a record or a record component
- a record representation clause, when the object is a record or a record component
- a size specification, in any case.

For each class of types the effect of a size specification alone is described. Interference between size specifications, packing and record representation clauses is described under array and record types.

4.1 Enumeration Types

Internal codes of enumeration literals

When no enumeration representation clause applies to an enumeration type, the internal code associated with an enumeration literal is the position number of the enumeration literal. Then, for an enumeration type with n elements, the internal codes

are the integers 0, 1, 2, ..., n-1.

An enumeration representation clause can be provided to specify the value of each internal code as described in [13.3]. The Alsys compiler fully implements enumeration representation clauses.

As internal codes must be machi: e integers the internal codes provided by an enumeration representation clause must be in the range -231.. 231-1.

Encoding of enumeration values

An enumeration value is always represented by its internal code in the program generated by the compiler.

When an enumeration type is not a boolean type or is a boolean type with an enumeration representation clause, binary code is used to represent internal codes. Negative codes are then represented using two's complement.

When a boolean type has no enumeration representation clause, the internal code 0 is represented by a succession of 0s and the internal code 1 is represented by a succession of 1s. The length of this pattern of 0s or of 1s is the size of the boolean value.

4.2 Integer Types

Predefined integer types

There are three predefined integer types in the Alsys implementation for MC680X0 machines:

```
type SHORT_SHORT_INTEGER is range -2**7 .. 2**7 -1;
type SHORT_INTEGER is range -2**15 .. 2**15 -1;
type INTEGER is range -2**31 .. 2**31 -1;
```

Selection of the parent of an integer type

An integer type declared by a declaration of the form:

```
type T is range L.. R;
```

is implicitly derived from a predefined integer type. The compiler automatically selects the predefined integer type whose range is the shortest that contains the values L to R

inclusive.

Encoding of integer values

Binary code is used to represent integer values. Negative numbers are represented using two's complement.

4.3 Floating Point Types

Predefined floating point types

There are two predefined floating point types in the Alsys implementation for MC680X0 machines:

```
type FLOAT is
digits 6 range -(2.0 - 2.0**(-23))*2.0**127 .. (2.0 - 2.0**(-23))*2.0**127;
type LONG_FLOAT is
digits 15 range -(2.0 - 2.0**(-51))*2.0**1023 .. (2.0 - 2.0**(-51))*2.0**1023;
```

Selection of the parent of a floating point type

A floating point type declared by a declaration of the form:

```
type T is digits D [range L .. R];
```

is implicitly derived from a predefined floating point type. The compiler automatically selects the smallest predefined floating point type whose number of digits is greater than or equal to D and which contains the values L to R inclusive.

Encoding of floating point values

In the program generated by the compiler, floating point values are represented using the IEEE standard formats for single and double floats.

The values of the predefined type FLOAT are represented using the single float format. The values of the predefined type LONG_FLOAT are represented using the double float

format. The values of any other floating point type are represented in the same way as the values of the predefined type from which it derives, directly or indirectly.

4.4 Fixed Point Types

Small of a fixed point type

If no specification of small applies to a fixed point type, then the value of small is determined by the value of delta as defined by [3.5.9].

A specification of small can be used to impose a value of small. The value of small is required to be a power of two.

Predefined fixed point types

To implement fixed point types, the Alsys compiler for MC680X0 machines uses a set of anonymous predefined types of the form:

```
type FIXED_8 is delta D range (-2**07-1)*S... 2**07*S; for FIXED_8'SMALL use S;

type FIXED_16 is delta D range (-2**15-1)*S... 2**15*S; for FIXED_16'SMALL use S;

type FIXED_32 is delta D range (-2**31-1)*S... 2**31*S; for FIXED_32'SMALL use S;
```

where D is any real value and S any power of two less than or equal to D.

Encoding of fixed point values

In the program generated by the compiler, a safe value V of a fixed point subtype F is represented as the integer:

V/F'BASE'SMALL

4.5 Access Types

Collection Size

When no specification of collection size applies to an access type, no storage space is reserved for its collection, and the value of the attribute STORAGE_SIZE is then 0.

As described in [13.2], a specification of collection size can be provided in order to reserve storage space for the collection of an access type. The Alsys compiler fully implements this kind of specification.

Encoding of access values.

Access values are machine addresses.

4.6 Task Types

Storage for a task activation

When no length clause is used to specify the storage space to be reserved for a task activation, the storage space indicated at bind time is used for this activation.

As described in [13.2], a length clause can be used to specify the storage space for the activation of each of the tasks of a given type. In this case the value indicated at bind time is ignored for this task type, and the length clause is obeyed.

Encoding of task values.

Encoding of a task value is not described here.

4.7 Array Types

Size of an array subtype

The size of an array subtype is obtained by multiplying the number of its components by the sum of the size of the components and the size of the gaps (if any). If the subtype is unconstrained, the maximum number of components is considered.

The size of an array subtype cannot be computed at compile time

- if it has non-static constraints or is an unconstrained array type with non-static index subtypes (because the number of components can then only be determined at run time).
- if the components are records or arrays and their constraints or the constraints of their subcomponents (if any) are not static (because the size of the components and the size of the gaps can then only be determined at run time).

As has been indicated above, the effect of a pragma PACK on an array type is to suppress the gaps and to reduce the size of the components. The consequence of packing an array type is thus to reduce its size.

If the components of an array are records or arrays and their constraints or the constraints of their subcomponents (if any) are not static, the compiler ignores any pragma PACK applied to the array type but issues a warning message. Apart from this

limitation, array packing is fully implemented by the Alsys compiler.

A size specification applied to an array type or first named subtype has no effect. The only size that can be specified using such a length clause is its usual size. Nevertheless, such a length clause can be useful to verify that the layout of an array is as expected by the application.

4.8 Record Types

Implicit components

In some circumstances, access to an object of a record type or to its components involves computing information which only depends on the discriminant values. To avoid useless recomputation the compiler stores this information in the record objects, updates it when the values of the discriminants are modified and uses it when the objects or its components are accessed. This information is stored in special components called implicit components.

An implicit component may contain information which is used when the record object or several of its components are accessed. In this case the component will be included in any record object (the implicit component is considered to be declared before any variant part in the record type declaration). There can be two components of this kind; one is called RECORD_SIZE and the other VARIANT_INDEX.

On the other hand an implicit component may be used to access a given record component. In that case the implicit component exists whenever the record component exists (the implicit component is considered to be declared at the same place as the record component). Components of this kind are called ARRAY_DESCRIPTORs or RECORD_DESCRIPTORs.

RECORD_SIZE

This implicit component is created by the compiler when the record type has a variant part and its discriminants are defaulted. It contains the size of the storage space necessary to store the current value of the record object (note that the storage effectively allocated for the record object may be more than this).

The value of a RECORD_SIZE component may denote a number of bits or a number of storage units. In general it denotes a number of storage units, but if any component clause specifies that a component of the record type has an offset or a size which cannot

be expressed using storage units, then the value designates a number of bits.

The implicit component RECORD_SIZE must be large enough to store the maximum size of any value of the record type. The compiler evaluates an upper bound MS of this size and then considers the implicit component as having an anonymous integer type whose range is 0... MS.

If R is the name of the record type, this implicit component can be denoted in a component clause by the implementation generated name R'RECORD SIZE.

VARIANT_INDEX

This implicit component is created by the compiler when the record type has a variant part. It indicates the set of components that are present in a record value. It is used when a discriminant check is to be done.

ARRAY_DESCRIPTOR

An implicit component of this kind is associated by the compiler with each record component whose subtype is an anonymous array subtype that depends on a discriminant of the record. It contains information about the component subtype.

The structure of an implicit component of kind ARRAY_DESCRIPTOR is not described in this documentation. Nevertheless, if a programmer is interested in specifying the location of a component of this kind using a component clause, he can obtain the size of the component using the ASSEMBLY parameter in the COMPILE command.

The compiler treats an implicit component of the kind ARRAY_DESCRIPTOR as having an anonymous array type. If C is the name of the record component whose subtype is described by the array descriptor, then this implicit component can be denoted in a component clause by the implementation generated name C'ARRAY_DESCRIPTOR.

• RECORD_DESCRIPTOR

An implicit component of this kind is associated by the compiler with each record component whose subtype is an anonymous record subtype that depends on a discriminant of the record. It contains information about the component subtype.

The structure of an implicit component of kind RECORD_DESCRIPTOR is not described in this documentation. Nevertheless, if a programmer is interested in specifying the location of a component of this kind using a component clause, he can

obtain the size of the component using the ASSEMBLY parameter in the COMPILE command.

The compiler treats an implicit component of the kind RECORD_DESCRIPTOR as having an anonymous array type. if C is the name of the record component whose subtype is described by the record descriptor, then this implicit component can be denoted in a component clause by the implementation generated name C'RECORD_DESCRIPTOR.

Size of a record subtype

Unless a component clause specifies that a component of a record type has an offset or a size which cannot be expressed using storage units, the size of a record subtype is rounded up to the a whole number of storage units.

The size of a constrained record subtype is obtained by adding the sizes of its components and the sizes of its gaps (if any). This size is not computed at compile time

- when the record subtype has non-static constraints,
- when a component is an array or a record and its size is not computed at compile time.

The size of an unconstrained record subtype is obtained by adding the sizes of the components and the sizes of the gaps (if any) of its largest variant. If the size of a component or of a gap cannot be evaluated exactly at compile time an upper bound of this size is used by the compiler to compute the subtype size.

A size specification applied to a record type or first named subtype has no effect. The only size that can be specified using such a length clause is its usual size. Nevertheless, such a length clause can be useful to verify that the layout of a record is as expected by the application.

Alignment of a record subtype

When no record representation clause applies to its base type, a record subtype is even byte aligned if it contains a component whose subtype is even byte aligned. Otherwise the record subtype is byte aligned.

When a record representation clause that does not contain an alignment clause applies to its base type, a record subtype is even byte aligned if it contains a component whose subtype is even byte aligned and whose offset is a multiple of 16 bits. Otherwise the

record subtype is byte aligned.

When a record representation clause that contains an alignment clause applies to its base type, a record subtype has an alignment that obeys the alignment clause. An alignment clause can specify that a record type is byte aligned or even byte aligned.

IMPLEMENTATION-DEPENDENT COMPONENTS

The following forms of implementation-generated names [13.4(8)] are used to denote implementation-dependent record components, as described in Section 4.8 in the paragraph on indirect and implicit components:

C'OFFSET R'RECORD_SIZE R'VARIANT_INDEX R'ARRAY_DESCRIPTORS R'RECORD_DESCRIPTORS

where C is the name of a record component and R the name of a record type.

ADDRESS CLAUSES

An address clause can be used to specify the address of an object, a program unit or an entry.

6.1 Address Clauses for Objects

An address clause can be used to specify an address for an object as described in [13.5]. When such a clause applies to an object no storage is allocated for it in the program generated by the compiler. The program accesses the object by using the address specified in the clause.

An address clause is not allowed for task objects, for unconstrained records whose size is greater than 8 kb, or for a constant.

Note that the function SYSTEM.VALUE, defined in the package SYSTEM, is available to convert a STRING value into a value of type SYSTEM.ADDRESS, also, the IMPORT attribute is available to provide the address of an external symbol. (Refer to Chapter 3 and section 2.3)

6.2 Address Clauses for Program Units

Address clauses for program units are not implemented in the current version of the compiler.

6.3 Address Clauses for Entries

An address clause may be used to associate an entry with a UNIX signal. (See Application Developer's Guide for detailed information.)

UNCHECKED CONVERSIONS

Unchecked type conversions are described in [13.10.2]. The following restrictions apply to their use.

Unconstrained arrays are not allowed as target types. Unconstrained record types without defaulted discriminants are not allowed as target types. Access types to unconstrained arrays are not allowed as target or source types. Note also that UNCHECKED_CONVERSION cannot be used for an access to an unconstrained string.

However, if the source and the target types are each scalar or access types, the sizes of the objects of the source and target types must be equal.

If a composite type is used either as source type or as target type this restriction on the size does not apply.

If the source and the target types are each of scalar or access type or if they are both of composite type, the effect of the function is to return the operand.

In other cases the effect of unchecked conversion can be considered as a copy:

- If an unchecked conversion is achieved of a scalar or access source type to a composite target type, the result of the function is a copy of the source operand. The result has the size of the source.
- If an unchecked conversion is achieved of a composite source type to a scalar or
 access target type, the result of the function is a copy of the source operand. The
 result has the size of the target.

INPUT-OUTPUT CHARACTERISTICS

In this part of the Appendix the implementation-specific aspects of the input-output system are described.

8.1 Introduction

In Ada, input-output operations are considered to be performed on objects of a certain file type rather than being performed directly on external files. An external file is anything external to the program that can produce a value to be read or receive a value to be written. Values transferred for a given file must be all of one type.

Generally, in Ada documentation, the term file refers to an object of a certain file type, whereas a physical manifestation is known as an external file. An external file is characterized by

- its NAME, which is a string defining a legal path name under the current version of the operating system
- its FORM, which gives implementation-dependent information on file characteristics.

Both the NAME and the FORM appear explicitly as parameters of the Ada procedures CREATE and OPEN. Though a file is an object of a certain file type, ultimately the object has to correspond to an external file. Both CREATE and OPEN associate a NAME of an external file (of a certain FORM) with a program file object.

Ada input-output operations are provided by means of standard packages ([14]):

SEQUENTIAL 10 A generic package for sequential files of a single element type.

DIRECT_IO A generic package for direct (random) access files.

TEXT 10

A generic package for human-readable files (text, ASCII).

(Please note that trying to apply TEXT_IO.NAME or TEXT_IO.FORM to STANDARD INPUT or

STANDARD_OUTPUT will raise USE_ERROR. Though it

may surprise the user, [14.4(5)] allows this behavior.)

IO EXCEPTIONS

A package which defines the exceptions needed by the above three packages.

The generic package LOW_LEVEL_IO is not implemented in this version.

The upper bound for index values in DIRECT_IO and for line, column and page numbers in TEXT_IO is given by

COUNT'LAST = 2**31-1

The upper bound for field widths in TEXT_IO is given by

FIELD'LAST = 255

8.2 The Parameter FORM

The parameter FORM of both the procedures CREATE and OPEN in Ada specifies the characteristics of the external file involved.

The procedure CREATE establishes a new external file, of a given NAME and FORM, and associates it with a specified program file object. The external file is created (and the file object set) with a specified (or default) file mode. If the external file already exists, the file will be erased. The exception USE ERROR is raised if the file mode is IN FILE.

Example:

```
CREATE(F, OUT_FILE, NAME => "MY_FILE",
FORM =>
"WORLD => READ, OWNER => READ_WRITE");
```

The procedure OPEN associates an existing external file, of a given NAME and FORM, with a specified program file object. The procedure also sets the current file mode. If there is an inadmissible change of mode, then the exception USE_ERROR is raised.

The parameter FORM is a string, formed from a list of attributes, with attributes

separated by commas. The string is not case sensitive (so that, for example, HERE and here are treated alike). (FORM attributes are distinct from Ada attributes.) The attributes specify:

- File protection
- . File sharing
- File structure
- Buffering
- Appending
- Blocking
- Terminal input

The general form of each attribute is a keyword followed by => and then a qualifier. The arrow and qualifier may sometimes be omitted. The format for an attribute specifier is thus either of

KEYWORD

KEYWORD = > QUALIFIER